

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

COSMO CL-300.150

(COSMOFEN 60)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Cleaning product

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Weiss Chemie + Technik GmbH & Co.KG, Hansastrasse 2, D-35708 Haiger
 Telephone: +49(0)2773/815-0, Fax:
 msds@weiss-chemie.de
 www.weiss-chemie.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (WIC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|--------------|-----------------|---|
| Flam. Liq. | 2 | H225-Highly flammable liquid and vapour. |
| Skin Irrit. | 2 | H315-Causes skin irritation. |
| Asp. Tox. | 1 | H304-May be fatal if swallowed and enters airways. |
| STOT SE | 3 | H336-May cause drowsiness or dizziness. |
| Aquatic | 2 | H411-Toxic to aquatic life with long lasting effects. |
| Chronic | | |

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

F, Highly flammable, R11
 Xi, Irritant, R38
 N, Dangerous for the environment, R51-53
 Xn, Harmful, R65
 R67

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

Hazard statement

H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

Prevention

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves and eye protection/face protection.

Response

P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P312-Call a POISON CENTER/doctor if you feel unwell.

Storage

P403+P233-Store in a well-ventilated place. Keep container tightly closed.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

REGULATION (EC) No 648/2004

30 % and more
 aliphatic hydrocarbons

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane | |
|--|---|
| Registration number (REACH) | 01-2119475514-35-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 921-024-6 (REACH-IT List-No.) |
| CAS | --- |
| content % | 80-<100 |
| Classification according to Directive 67/548/EEC | Highly flammable, F, R11 Irritant, Xi, R38 Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R67 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 |

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16. The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Headaches

Dizziness

Effects/damages the central nervous system

Coordination disorders

Unconsciousness

Ingestion:

Nausea

Vomiting

Danger of aspiration

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

Pulmonary oedema prophylaxis

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Extinguishing powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Explosive vapour/air mixture

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

GB

Page 2 of 4
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 12.06.2014 / 0005
 Replaces revision of / Version: 26.05.2014 / 0004
 Valid from: 12.06.2014
 PDF print date: 17.06.2014
 COSMO CL-300.150

(COSMOFEN 60)

Keep non-essential personnel away.
 Remove possible causes of ignition - do not smoke.
 Ensure sufficient supply of air.
 Avoid inhalation, and contact with eyes or skin.
 If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.
 Resolve leaks if this possible without risk.
 Prevent surface and ground-water infiltration, as well as ground penetration.
 Prevent from entering drainage system.
 If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid inhalation of the vapours.
 Ensure good ventilation.
 If applicable, suction measures at the workstation or on the processing machine necessary.
 Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Avoid contact with eyes or skin.
 Handle and open container with care.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").
 Do not store with flammable or self-igniting materials.

Solvent resistant floor
 Protect from direct sunlight and warming.
 Store cool
 Store in a dry place.

7.3 Specific end use(s)

Cleaning product

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 600 mg/m³

| Chemical Name | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane | Content %:80- <100 |
|--------------------------------|--|--------------------|
| WEL-TWA: 600 mg/m ³ | WEL-STEL: --- | --- |
| BMGV: --- | Other information: --- | |

GB

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Solvent resistant protective gloves (EN 374).
 Recommended
 Protective nitrile gloves (EN 374)
 Protective Viton® / fluoroelastomer gloves (EN 374)
 Minimum layer thickness in mm:
 >= 0,50
 Permeation time (penetration time) in minutes:
 >= 480
 The breakthrough times determined in accordance with EN 374 Part III were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Solvent resistant protection clothing (EN 13034)

Respiratory protection:
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state: | Liquid |
| Colour: | Colourless |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | n.a. |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | 78 - 113 °C |
| Flash point: | < -18 °C |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | n.a. |
| Lower explosive limit: | 0,8 Vol-% |
| Upper explosive limit: | 7,7 Vol-% |
| Vapour pressure: | 61 hPa (20°C) |
| Vapour density (air = 1): | Not determined |
| Density: | -0,71 g/cm ³ (20°C) |
| Bulk density: | n.a. |
| Solubility(ies): | Not determined |
| Water solubility: | Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | n.a. |
| Decomposition temperature: | Not determined |
| Viscosity: | <7 mm ² /s (40°C) |
| Explosive properties: | Product is not explosive. When using: development of explosive vapour/air mixture possible. |
| Oxidising properties: | No |
| 9.2 Other information | |
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | >99 % (Organic solvents) |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.
 Heating, open flame, ignition sources
 Electrostatic charge

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

COSMO CL-300.150

(COSMOFEN 60)

| Toxicity/effect | End point | Value | Unit | Organism | Test method | Notes |
|---|-----------|-------|------|----------|-------------|--------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |

(GB)

Page 3 of 4
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 12.06.2014 / 0005
 Replaces revision of / Version: 26.05.2014 / 0004
 Valid from: 12.06.2014
 PDF print date: 17.06.2014
 COSMO CL-300.150

(COSMOFEN 60)

| | | | | | | |
|---|--|--|--|--|--|--|
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Respiratory tract irritation: | | | | | | n.d.a. |
| Repeated dose toxicity: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |
| Other information: | | | | | | Classification according to calculation procedure. |

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Toxicity/effect | End point | Value | Unit | Organism | Test method | Notes |
|------------------------------------|-----------|-------|---------|----------|-------------|----------------------------------|
| Acute toxicity, by oral route: | LD50 | >5840 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >2920 | mg/kg | Rat | | |
| Acute toxicity, by inhalation: | LC50 | 25,2 | mg/l/4h | Rat | | |
| Skin corrosion/irritation: | | | | | | Irritant |
| Serious eye damage/irritation: | | | | | | Slightly irritant |
| Respiratory or skin sensitisation: | | | | | | Not sensitising |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | may cause headaches and vertigo. |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

COSMO CL-300.150

(COSMOFEN 60)

| Toxicity/effect | End point | Time | Value | Unit | Organism | Test method | Notes |
|-------------------------------------|-----------|------|-------|------|----------|-------------|--------|
| Toxicity to fish: | | | | | | | n.d.a. |
| Toxicity to daphnia: | | | | | | | n.d.a. |
| Toxicity to algae: | | | | | | | n.d.a. |
| Persistence and degradability: | | | | | | | n.d.a. |
| Bioaccumulative potential: | | | | | | | n.d.a. |
| Mobility in soil: | | | | | | | n.d.a. |
| Results of PBT and vPvB assessment: | | | | | | | n.d.a. |
| Other adverse effects: | | | | | | | n.d.a. |

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Toxicity/effect | End point | Time | Value | Unit | Organism | Test method | Notes |
|----------------------|-----------|------|-------|------|---------------------------------|-------------|---------------------------------------|
| Toxicity to fish: | LL50 | 96h | 11,4 | mg/l | | | Goldförelle (Oncorhynchus aquabonita) |
| Toxicity to daphnia: | EL50 | 48h | 3 | mg/l | Daphnia magna | | |
| Toxicity to algae: | EL50 | 72h | 30 | mg/l | Pseudokirchneriella subcapitata | | |

SECTION 13: Disposal considerations**13.1 Waste treatment methods****For the substance / mixture / residual amounts**

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

07 01 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixes

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 01 paper and cardboard packaging

15 01 04 metallic packaging

SECTION 14: Transport information**General statements**

UN number: 3295

Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 3295 HYDROCARBONS, LIQUID, N.O.S. (SPECIAL PROVISION 640D)

Transport hazard class(es):

Packing group: II

Classification code: F1

LQ (ADR 2013): 1 L
 LQ (ADR 2009): 4
 Environmental hazards: environmentally hazardous
 Tunnel restriction code: D/E

Transport by sea (IMDG-code)

UN proper shipping name:

HYDROCARBONS, LIQUID, N.O.S. (HYDROCARBONS, C6-C7)

Transport hazard class(es):

Packing group: II

EmS: F-E, S-D

Marine Pollutant: Yes

Environmental hazards: environmentally hazardous

Transport by air (IATA)

UN proper shipping name:

Hydrocarbons, liquid, n.o.s.

Transport hazard class(es):

Packing group: II

Environmental hazards: Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

For classification and labelling see Section 2.

Observe restrictions: Yes

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Observe law on protection of expectant mothers (German regulation).

VOC (1999/13/EG): 705 g/l (100 %)

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections:

15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|--|
| Flam. Liq. 2, H225 | Classification based on test data. |
| Skin Irrit. 2, H315 | Classification according to calculation procedure. |
| Asp. Tox. 1, H304 | Classification according to calculation procedure. |
| STOT SE 3, H336 | Classification according to calculation procedure. |
| Aquatic Chronic 2, H411 | Classification according to calculation procedure. |

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

11 Highly flammable.

38 Irritating to skin.

51 Toxic to aquatic organisms.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

| | |
|----------------|---|
| AC | Article Categories |
| acc., acc. to | according, according to |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| ADR | Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) |
| AOEL | Acceptable Operator Exposure Level |
| AOX | Adsorbable organic halogen compounds |
| approx. | approximately |
| Art., Art. no. | Article number |
| ATE | Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) |
| BAM | Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) |
| BAuA | Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) |
| BCF | Bioconcentration factor |
| BGV | Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) |
| BHT | Butylhydroxytoluol (= 2,6-Di- <i>t</i> -butyl-4-methyl-phenol) |
| BMGV | Biological monitoring guidance value (EH40, UK) |
| BOD | Biochemical oxygen demand |
| BSEF | Bromine Science and Environmental Forum |
| bw | body weight |
| CAS | Chemical Abstracts Service |
| CEC | Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids |

(GB)

Page 4 of 4

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 12.06.2014 / 0005

Replaces revision of / Version: 26.05.2014 / 0004

Valid from: 12.06.2014

PDF print date: 17.06.2014

COSMO CL-300.150

(COSMOFEN 60)

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (= Technical Regulations for Hazardous Substances)
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
 WHO World Health Organization
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.