

PRODUCT BULLETIN

Roto TSL with Low Handle Height

Temporary image



Roto TSL with Low Handle Height

Roto have now introduced a low handle height version of their excellent TSL twin-cam security lock for outward opening windows.

The handle position is offset towards the bottom of the TSL (205mm from the end) in order to make operating the window easier in situations where reaching a handle fitted in the centre of the sash is difficult. This could be because the window is tucked away in a deep reveal, it's positioned behind kitchen or bathroom fittings, or if the user is wheelchair-bound.

The Lifetime Homes Window Specification states that wheelchair users should be able to see out of a window when seated and that they should be able to operate at least one window in each room from their chair. To achieve this, the specification calls for at least one window in each room to have a handle or control positioned no higher than 1200mm from floor level. TSL with low handle height makes this possible while providing locking points right to the top of the window as normal.

All other aspects of the new product are exactly the same as on the standard TSL, so all the benefits of Roto TSL, such as the EN 1670 class 5 salt spray and PAS 24 security test results, still apply.

Benefits at a glance:

- 205mm gearbox position meets requirements of Lifetime Homes standard
- Secure window locking system tested to security standard PAS24:2012
- Fits Eurogrooves up to 1600mm
- Quick to fit - no cropping or fitting of extension/end pieces is required and all fasteners are applied from same direction
- Nano Sil surface treatment meets requirements of EN1670:2007 grade 5 (480 hours)
- NT faceplate for greater tolerance and pleasing aesthetics
- 10 year Roto functional warranty

Length	MB*	20BS/8MB	20BS/9.5MB	22BS/8MB	22BS/9.5MB	Box Qty
850mm	4	2RWE4561	2RWE4565	2RWE4569	2RWE4573	10
950mm	4	2RWE4562	2RWE4566	2RWE4570	2RWE4574	10
1050mm	4	2RWE4563	2RWE4567	2RWE4571	2RWE4575	10
1150mm	4	2RWE4564	2RWE4568	2RWE4572	2RWE4576	10

*Denotes quantity of striker plates required

E &OE
CUS PB 290416

VBH (GB) Ltd
VBH House, Bailey Drive,
Gillingham Business Park,
Gillingham, Kent
ME8 0WG
Tel: 01634 263263
Fax: 01634 263504
Email: sales@vbhgb.com
Online: www.vbhgb.com

